

Reference Values provided by DYMIND

Von-Langen-Weg 10 48565 Steinfurt / Germany

Tel.: 02551/2097 Fax: 02551/80883 E-Mail: info@keul.de Internet: www.keul.de

CALIBRATOR

LOT PLUS0424

M 2024-03-12

□ 2024-05-05

| | 1 - | | ¥ 2024-0 | |
|------------------------------------------------------------------------------------------------------------------------------------|-----------|----------------------|-----------------|--|
| Applicable Instruments | Parameter | Unit | Reference Value | |
| DH31, DH33, DH36 (Technical File Version A5.0 or higher) DH31 Vet, DH36 Vet (Technical File Version A1.0 to A4.0) Hem-o-test 3600 | WBC | ×10 ⁹ /L | 9.27 | |
| | RBC | ×10 ¹² /L | 4.71 | |
| | HGB | g/L | 135 | |
| | MCV | fL | 93.3 | |
| | PLT | ×10 ⁹ /L | 238 | |
| DH21, DH23 DH25, DH26 (Technical File Version A1.0 or higher) | WBC | ×10 ⁹ /L | 9.17 | |
| | RBC | ×10 ¹² /L | 4.52 | |
| | HGB | g/L | 135 | |
| | MCV | fL | 86.4 | |
| | PLT | ×10 ⁹ /L | 239 | |
| DH20, DH22 (Technical File Version B1.0 or higher) | WBC | ×10 ⁹ /L | 9.35 | |
| | RBC | ×10 ¹² /L | 4.58 | |
| | HGB | g/L | 136 | |
| | MCV | fL | 90.8 | |
| | PLT | ×10 ⁹ /L | 237 | |
| DH31 Vet, DH36 Vet (Technical File Version A5.0 or higher) | WBC | ×10 ⁹ /L | 9.20 | |
| | RBC | ×10 ¹² /L | 4.52 | |
| | HGB | g/L | 130 | |
| | MCV | fL | 93.6 | |
| | PLT | ×10 ⁹ /L | 236 | |

[NOTE]

- 1. The calibrator should be stored in refrigerator ($2^{\circ}C \sim 8^{\circ}C$). After opening, it will keep stable for 7 days when it is stored airtight at $2^{\circ}C \sim 8^{\circ}C$.
- 2. Before mixing and running the calibrator after take it out from the refrigerator, please keep it at least 15 minutes until reaching room temperature (15°C \sim 30°C).
- 3. Calibrator must be well mixed before using. Please mix gently, to avoid cells rupture and/or generating bubbles.
- 4. After using, put the calibrator back into the refrigerator to prevent contamination and evaporation.



Reference Values provided by DYMIND

Von-Langen-Weg 10 48565 Steinfurt / Germany

Tel.: 02551/2097 Fax: 02551/80883 E-Mail: info@keul.de Internet: www.keul.de

CALIBRATOR

LOT PLUS0424

M 2024-03-12

2024-05-05

| Applicable Instruments | Parameter | Unit | Reference Value |
|-------------------------------------------------------|-----------|----------------------|-----------------|
| DH36X (Technical File Version A1.0 or higher) | WBC | ×10 ⁹ /L | 9.63 |
| | RBC | ×10 ¹² /L | 4.63 |
| | HGB | g/L | 136 |
| | MCV | fL | 89.9 |
| | PLT | ×10 ⁹ /L | 234 |
| DP-H10 Vet (Technical File Version A1.0 or higher) | WBC | ×10 ⁹ /L | 9.19 |
| | RBC | ×10 ¹² /L | 4.52 |
| | HGB | g/L | 140 |
| | MCV | fL | 93.6 |
| | PLT | ×10 ⁹ /L | 236 |

[NOTE]

- 1. The calibrator should be stored in refrigerator ($2^{\circ}\text{C} 8^{\circ}\text{C}$). After opening, it will keep stable for 7 days when it is stored airtight at $2^{\circ}\text{C} 8^{\circ}\text{C}$.
- 2. Before mixing and running the calibrator after take it out from the refrigerator, please keep it at least 15 minutes until reaching room temperature (15 $^{\circ}$ C $^{\circ}$ 30 $^{\circ}$).
- 3. Calibrator must be well mixed before using. Please mix gently, to avoid cells rupture and/or generating bubbles.
- 4. After using, put the calibrator back into the refrigerator to prevent contamination and evaporation.